

## Pipe Rigging Rollers



### ProStar™ Beam Clamp Rigging Rollers

Pipe rigging rollers are used for a variety of applications, particularly so for pipe rack installation at power plants, refineries, and other industrial facilities. ProStar pipe rigging rollers are designed to be lightweight, with beam clamps for quick installation. Various roller head options ensure pipe can be easily, safely, and efficiently installed.



SPECIFICATIONS	1-TON UNIDIRECTIONAL PRSHZD12100	1-TON UNIDIRECTIONAL PRSHZ6200	2-TON UNIDIRECTIONAL PRSHZ2100	5-TON UNIDIRECTIONAL PRSHZD100	10-TON UNIDIRECTIONAL PRSHZDD60200
LOAD CAPACITY	2,000 lbs.	2,000 lbs.	4,000 lbs.	10,000 lbs.	20,000 lbs.
DIAMETER RANGE	2 in. - 12 in.	2-3/8 in. - 24 in.	2 in. - 16 in. (2 - 32 in. optional)	2 in. - 42 in.	24 in. - 60 in.
SHIPPING WEIGHT	43 lbs.	94 lbs.	98 lbs.	95 lbs.	222 lbs.
SHIPPING DIMENSIONS	15 in. x 10 in. x 5 in.	26 in. x 15 in. x 9 in.	31 in. x 19 in. x 26 in.	26 in. x 15 in. x 7 in.	41 in. x 16 in. x 11 in.
BEAM CLAMP FLANGE WIDTH	5 in. - 12 in.	5 in. - 12 in.	5 in. - 12 in.	5 in. - 12 in.	5 in. - 12 in.



SPECIFICATIONS	1-TON MULTIDIRECTIONAL PRSHZD12100	1-TON MULTIDIRECTIONAL PRSHZ6200	2-TON MULTIDIRECTIONAL PRSHZDD60200
LOAD CAPACITY	2,000 lbs.	2,000 lbs.	4,000 lbs.
DIAMETER RANGE	2 in. - 8 in.	2 in. - 24 in.	4 in. - 36 in.
SHIPPING WEIGHT	40 lbs.	60 lbs.	80 lbs.
SHIPPING DIMENSIONS	15 in. x 9 in. x 5 in.	15 in. x 22 in. x 6 in.	18 in. x 31 in. x 7 in.
BEAM CLAMP FLANGE WIDTH	5 in. - 12 in.	5 in. - 12 in.	5 in. - 12 in.

Specifications subject to change without notice. Consult your Praxair representative when ordering.

High-grade urethane rolls for grip, protecting pipe coatings and shock absorption.

Quick clamp system for 5 to 12 inches structural beam flange range.



Available with jacking system to load or offload rollers easily.