

ProStar™ PRSHDJ Roller Supports

Rigid Construction, Maximum Flexibility

For positioning pipe up to 48 inches OD, *ProStar* modular stands and rollers deliver high productivity and reliable, heavy-duty service. For maximum functionality indoors and at the job site, *ProStar* pipe and roller stands allow you to choose multiple top and/or bottom configurations.

HDJ heavy-duty roller supports offer an even wider range of capabilities such as geared height adjustability, braking base casters, ratchet hold down straps, fork lift pockets and ultra tough frame design.

ProStar Folding & Solid Tripod Stands

ProStar PRS LD and *PRS TS3* super-duty modular tripod stands are available with standard v-head and/or customer's choice of roller tops or base options. Call your Praxair representative for order assistance.



SPECIFICATIONS	PRSLD255100 ROLLER TRIPOD	PRSTS3160V	PRSTS3280V	PRSTS3330V
LOAD CAPACITY	2,500 lbs.	5,000 lbs.	5,000 lbs.	5,000 lbs.
DIAMETER RANGE	2 in. - 28 in.	2 in. - 28 in.	2 in. - 28 in.	2 in. - 28 in.
HEIGHT RANGE	21 in. - 33 in.	16 in. - 25 in.	28 in. - 44 in.	33 in. - 56 in.
SHIPPING DIMENSIONS	23 in. × 26 in. × 26 in.	26 in. × 26 in. × 21 in.	33 in. × 33 in. × 21 in.	33 in. × 33 in. × 21 in.
SHIPPING WEIGHT	60 lbs.	39 lbs.	53 lbs.	58 lbs.

Specifications subject to change without notice. Consult your Praxair representative when ordering.

ProStar Gear-Height Roller Base



GEAR ELEVATED!



HEAVY-DUTY CONSTRUCTION

- Geared height adjust
- Rolling base
- Braking casters
- Ratchet and hold down strap
- Forklift pockets

SPECIFICATIONS	2-TON GEARED HEIGHT/ROLLER BASE PRSHDJ2C100	5-TON GEARED HEIGHT/ROLLER BASE PRSHDJ5C100
LOAD CAPACITY	4,000 lbs.	10,000 lbs.
DIAMETER RANGE	2 in. - 36 in.	4 in. - 48 in.
HEIGHT RANGE	27 in. - 39 in.	27 in. - 39 in.
SHIPPING DIMENSIONS	38 in. × 24 in. × 28 in. (top of wheel)	48 in. × 28 in. × 28 in. (top of wheel)
SHIPPING WEIGHT	191 lbs.	429 lbs.

Specifications subject to change without notice. Consult your Praxair representative when ordering.